

# Trac-Rite Roll-Up Door Accessories

## Jamb Brush Seal


**Description:** Weather strip fabricated from black polypropylene filament brush in a mill finish aluminum extrusion. Attaches to side jamb.



**Application:** Designed to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.

## Header Draft Stop (Field Installed)

**Description:** 4" wide, consists of a 1" rigid PVC strip and 3" flexible TPE section. Attaches to the header.



**Application:** Designed to seal the top of the door to eliminate air infiltration. Recommended for use in wide-open space, dusty weather conditions, and with the insulation accessory.

## Exterior Latch

**Description:** Cast zinc alloy with black nickel finish. Latch slide has magnetic properties for use with security system switches. Designed to accommodate two padlocks up to 7/16" shank. Accommodates Trac-Rite's optional SpaceGuard cylinder lock which features an easy over-lock system. The lock does not penetrate the door.



**Application:** Provides secure exterior locking capabilities to a single entrance.

## SpaceGuard Cylinder Lock

**Description:** Removable security cylinder features easy over-lock capability and protection from bolt cutters. Each cylinder lock comes with three coded keys.



**Application:** Provides added security, especially for unfenced areas.


## Hood

**Description:** Covers the door nest and chain hoist. (Will not cover motor operator.) Available in Iced White only.

**Application:** Keeps the door nest clean, protects the mechanisms from weather, and aesthetically pleasing.

## Insulation (Factory Installed)


**Description:** Double bubble foil reflective insulation with an extra layer of polyurethane coating on the front side for durability.



**Application:** Helps maintain desired temperature in heated building applications.

## Interior Lock

**Description:** 12-gauge, zinc-coated steel slide bolt engages a lock strike attached to the side guide. Two locks per door fasten to the bottom assembly and are suitable for padlocking.



**Application:** Recommended where interior access is needed, for example, counter shutter applications.

## Shaft Extension Kit

**Description:** Shaft extensions are designed to fit the axle. Measures 1" in diameter with a 1/4" keyway.



**Application:** Necessary to install chain hoists or motor operators.

# Trac-Rite Roll-Up Door Accessories

## Narrow Jamb Bracket Plates

**Description:** Dimensions – 5" x 5-5/8"

**Application:** Increases jamb mounting surface width when necessary.

## Direct-Drive Chain Hoist

**Description:** 9-1/2" outside diameter cast iron pocket wheel with zinc-plated steel chain guide. Mounts on a 1" diameter shaft extension fastened to the door axle. Mounts on either side of the door. Chain keeper provided.

**Application:** Pulley system offers easy and convenient opening.

## 4:1 Reduced-Drive Chain Hoist

**Description:** Uses a chain and a two-sprocket arrangement to make the door much easier to lift. Mounts on a 1" diameter shaft extension fastened to the door axle. Mounts on either side of the door. Chain keeper provided.




**Application:** When opening large, heavy doors, this chain hoist fits the bill. For one pull, the door opens 1/4 revolution. This allows for controlled easy opening. Additionally, this hoist allows tall doors to open.



## Chain Tensioner

**Description:** This tensioner is designed to maintain tension on the hand chain for roll up doors. The tensioner wheel may be mounted to the wall or floor.

**Application:** The tensioner is recommended for use with any large Trac-Rite door equipped with a hand chain for lowering and raising the door. The tensioner prevents the chain from jumping the sprocket at the top of the door during operation, which can jam the door into place. It is most commonly used with the 977 door.



## MHS 150 Lift Master Medium-Duty Motor Operator

**Description:** 1/2" horsepower, medium-duty operator. Wall mounted, this operator drives a sprocket mounted on the shaft extension connected to the axle.

**Application:** Offers one-touch opening with several accessory options and has remote control capabilities. Ideal for extended operation (up to 12 cycles per hour).



## LJ8950 Lift Master Opener

**Description:** Ultra-quiet, space-saving, wall-mounted design. Specially designed for garages and unique applications that don't allow for a traditional garage door opener, such as garages with very low, cathedral or obstructed ceilings.

**Application:** Mounts on the left or right side of door. Easily program additional remotes, keypads and/or keyless entry. Optional EverCharge™ battery backup system opens door even when the power goes out.



## Reverse Rolled Curtain

**Description:** Finished material faces exterior.

**Application:** Use when exterior mounting is necessary due to lack of available head room for interior mounting. A hood may be necessary with this option.



### For more information

PHONE 800 448 8979  
FAX 800 236 8722  
WEBSITE [www.tracrite.com](http://www.tracrite.com)  
EMAIL [tr@tracrite.com](mailto:tr@tracrite.com)  
ADDRESS 314 Wilburn Road  
Sun Prairie, WI 53590

2269.mkt.0622